



SL-80 WATER BASED ACRYLIC FLOOR SEAL

PRODUCT DESCRIPTION:

SL-80 is a heavy duty, long wearing high gloss and high solids acrylic formula designed to give the “wet look” to unglazed quarry tile, clay tile, slate, brick pavers and Portland cement products. SL-80 needs no buffing and cleans easily with a damp mop. SL-80 is semi-buffable if desired. SL-80 provides an extremely hard, durable surface that allows the user to apply fewer coatings for a superior finish that outlasts other finishes, reducing the frequency of stripping/removing coatings. Hot cooking oils do not affect this product. SL-80 can be removed with SL-86 Floor Stripper.

USES:

SL-80 is designed for unglazed quarry tile, clay tile, slate, brick pavers and Portland cement products.

LIMITATIONS:

SL-80 is not to be used in areas subjected to frequent or prolonged wetting. Do not seal new grout joints until they have cured for 21 days minimum. ALWAYS TEST A SMALL AREA BEFORE GENERAL APPLICATION TO DETERMINE PROPER TECHNIQUES.

APPLICATION:

1. Be sure floor surface is clean, dry and free of any wax, grease or other sealers before applying SL-80.
2. If area was previously sealed with a wax or acrylic sealer, strip floor using a cleaner like SL-86 Floor Stripper.
3. Apply SL-80 with a lambs wool applicator, cotton string mop, sponge mop or soft brush.
4. Use smooth even strokes. Be careful not to create bubbles or puddles.
5. Do not pour unused sealer back into container or dilute with water or other chemicals.
6. Allow 2 hours to dry between coats. Allow 12 hours before opening to traffic.

Many thin coats applied with dry time between each coat will provide a more aesthetically pleasing final appearance. Applying SL-80 too thick in any one coat may cause a white haze to appear in the area(s) that is/are too thick.

COVERAGE:

	Sq. ft/gallon
Unglazed Quarry Tile	200-300
Slate	150-225

PACKAGING:

SL-80 is available in:
1-quart bottles
1-gallon bottles