



SL-99 SUMMITSEAL II

PRODUCT DESCRIPTION:

SummitSeal is an extremely effective water-repellant (hydrophobic) and oil-repellant (oleophobic) penetrating sealant for all types of unglazed ceramic tile, natural stone and cementitious grouts. It is water based and contains no organic solvent. It leaves little or no film residue and therefore leaves the stone, clay or masonry surface very natural in appearance. For all practical purposes this product is invisible. This product is ideally suited for long term protection from water borne stains, greasy food stains, paint drips, cosmetics and a wide range of graffiti. It will dramatically reduce the maintenance required to maintain exterior tile, mortar and natural stone surfaces subject to mineral deposition caused by exposure to hard water spray. Also useful to dramatically reduce efflorescence issues with retainer walls, walls, ceilings and floors.

USES:

Commercial flooring and kitchens: Terra cotta, quarry tile, slate, sandstone, porcelain pavers, marble, limestone, terrazzo tile, slab, Mexican saltillo, cantera stone, brick, granite counters and floors. Suitable for interior/exterior where water does not make long term puddles. Not for use in sealing tanks such as swimming pool basins.

APPLICATION:

Test sealer on your substrate before using to insure that any possible cosmetic changes or darkening are acceptable. Insure that surfaces to be treated are clean and dry (24 hours). If surface has been acid washed, ensure that all residues have been neutralized and rinsed clean. Wipe SL-99 onto surface with a clean white cloth. SL-99 can also be applied using a garden sprayer if precautions are taken to apply a sufficient and even coating, avoid overspray and spraying areas not to be sealed (such as tile joints not yet grouted), and avoid breathing atomized spray. Allow SL-99 to stand for 1 minute, and then wipe off. For best results, apply two coats and allow the coating to dry a minimum of 2 hours between coats. On horizontal or flooring surfaces, avoid standing puddles by wiping or sponging excess sealer from the surface before it dries. Wipe sealer off if not absorbed. Protect surrounding areas from splash and overspray. Do not allow sealant to come in contact with areas not to be sealed.

COVERAGE:

(Sq. ft. per gallon per coat)	
Honed Marble	500-800
Dense Quarry Tile	350-500
Porous Quarry Tile/Salttillo	100-250
Slate	300-400
Concrete (smooth)	100-300
Polished Granite	800-1000

PACKAGING:

1 gallon, 5 gallons

PRECAUTIONS:

Avoid skin and eye contact. Wear rubber gloves and goggles.

KEEP OUT OF REACH OF CHILDREN.