



SL-55 COLOR ENHANCING SEALER

PRODUCT DESCRIPTION:

SL-55 is a one part penetrating sealant for use on grout, stone and brick pointing mortar, porous stone, brick, and clay materials. SL-55 deepens and darkens the color of materials and provides a low gloss or sheen. This product is ideally suited for long-term hiding of waterborne stains and greasy food stains.

APPLICATION:

Test the sealer on a potential substrate before using to insure that the cosmetic changes will be suitable. Always test in an inconspicuous area or an extra piece of material. Insure that surfaces to be treated are clean and thoroughly dry. If surface(s) has/have been acid washed, be certain all residues have been neutralized and rinsed clean. SL-55 can be applied to cementitious grouts 14 days after installation of grout. While wearing latex or similar impervious gloves, wipe a thin, uniform coat onto surface with a clean cloth or brush. Wipe up all excess after permitting SL-55 to soak on floor for a few minutes. Dry excess can be removed with Summitville SL-100 Tile and Grout Cleaner. Allow floor to cure for one week uncovered, prior to cleaning floor. Do not use harsh cleaners for two weeks after application of SL-55. Summitville recommends application of SL-55 in sections to allow traffic through area while SL-55 is curing.

FIRST AID:

Keep out of reach of children.

Irritant to eyes and mucous membranes. Harmful if swallowed.

EYE CONTACT: Immediately flush with large amounts of water. Contact a physician if irritation persists.

SKIN CONTACT: Wash contaminated area with soap and water. Remove contaminated clothing.

INGESTION: If swallowed, drink large amounts of water or milk. See physician immediately. **DO NOT INDUCE VOMITING.**

PACKAGING:

SL-55 is available in:

1-quart units

1-gallon units

5-gallon units

COVERAGE:

	Approx tile coverage per coat, per gallon	Minimum Dry Hours @ 72°F After:	Minimum Hrs Before Floor Traffic @ 72°F:
Honed Marble	200-350 sq. ft	2-4	16
Dense Quarry Tile	150-225 sq. ft	3-5	16
Porous Quarry Tile	50-125 sq. ft	6-8	16
Slate	150-200 sq. ft	3-5	16
Concrete (smooth)	50-150 sq. ft	6-8	16
Polished Granite	400-500 sq. ft	2-4	16

Tile Size/Grout Only	Grout width 1/8" sq. ft per coat, per gallon	Grout width 1/4" sq. ft per coat, per gallon
4 x 4	2400	960
8 x 8	2960	1360
12 x 12	3200	1520
16 x 16	3600	1680