



## SL-100 TILE & GROUT CLEANER AND EPOXY FILM REMOVER

### PRODUCT DESCRIPTION:

SL-100 has a pleasant citrus scent and a removing strength comparable to methylene chloride, while being an environmentally responsible, natural, and sustainable product. SL-100 is also free of harsh mineral acids.

Restores old dirty tile and grout to “like new” condition, removes epoxy and urethane film from tile and is easy to use, fast and effective. SL-100 is useful in removing cured epoxy and urethane when used full strength and allowed to soak to soften the epoxy. The cured time of an epoxy or urethane does not matter; SL-100 will attack and soften the epoxy or urethane. SL-100 can also be used to remove some paint finishes. Do not use SL-100 on finishes over absorptive substrates such as wood. SL-100 is amber in color and may stain the wood or porous substrate if allowed to be absorbed. SL-100 will remove oil from non absorptive surfaces to be painted, sealed, or otherwise coated such as oil from metal parts including stainless steel. If using SL-100 on stainless steel, remember to coat stainless steel immediately after removing SL-100, or the stainless will rust quickly. SL-100 can be diluted into water as an environmentally responsible, natural, and sustainable general purpose cleaner. Dilute to your cleaning strength preference.

### CAUTIONS:

Do not allow product to come in contact with plastics, vinyl or painted surfaces. Always test an area before general application to ensure desired results will be obtained.

### APPLICATION:

1. Test cleaner in an inconspicuous area before general application and use.
2. Apply SL-100 at full strength to the tile and grout. Allow a 5-30 minute continually wet soak time. Do not exceed 30 minutes on epoxy grout unless you are attempting to remove an epoxy stain/layer. If removing an epoxy layer, you may exceed 30 minutes.
3. After dwell time, remove either manually with a brass cove brush, or for large areas use a floor scrubber with a brush or a high-pressure wash and a wet vacuum pick-up.
4. Allow the floor to dry and then detail any remaining spots using the manual method.
5. Rinse thoroughly with clean water and allow floor to dry.

### FIRST AID:

EYE CONTACT: Flush with plenty of water for 15 minutes, call a physician. SKIN CONTACT: Wash contacted area with soap and water, remove contaminated clothing. INGESTION: If swallowed, drink large amounts of water or milk. See physician immediately. Do not induce vomiting.

### AVAILABILITY:

1 quart, 1 gallon, and 5 gallon

### SHELF LIFE:

Two years from Date of Manufacture